

NEC MultiSync® EA224WMi

Order Code: 60003336 (BK), 60003337 (WH)

NEC LCD 21.5" Commercial Display

NEC MultiSync® EA224WMi features an extremely thin LED backlight panel with IPS technology which results in an ultra-modern and slim design in combination with a premium feature set for the corporate office use. Ambient Light and Human Sensors enforce the sustainable product concept while offering improved ergonomics with 130 mm height adjustability. Moreover the display offers broad connectivity with three inputs DisplayPort, DVID and D-Sub. Thanks to its excellent IPS image quality with wide viewing angles in 16:9 screen format, it offers a high level of ergonomic comfort.

Ideal for the corporate that demand style and future proof technology.



DELIVERING GENUINE BENEFITS

Ambient Light Sensor - with Auto Brightness function always sets optimised brightness level according to ambient light and content conditions.

Ergonomic Office - full height adjustability (130 mm), swivel, tilt and pivot functionality ensures perfect individual ergonomic set-up.

Feature Set for Perfect Office Use - Integrated Speakers, headphone jack and USB Hub provide excellent options for office communication.

Green Product Concept - Eco Mode and Carbon Footprint Meter / Carbon Savings Meter, Ambient Light Sensor.

Human Sensor - detects the presence of a person in front of the screen; display switches on/off automatically depending on the presence of the user.

Image display - 21.5inch 16:9 IPS with LED backlight.

Vesa Mount (100 mm) - allows to install the monitor via various mounting solutions.



OUTSTANDING PERFORMANCE

- **Ultra-modern and slim design.** The product design is discrete and puts priority on the screen image and function.
- **Ambient Light and Human Sensors.** The new sensor technologies provide a perfect image with minimum power consumption.
- **Improved ergonomics.** The ergonomic stand with 130 mm height adjustability allows greatest set-up flexibility.
- **Integrated Speakers,** headphone jack and USB Hub provide excellent options for office communication.
- **New Control Sync Feature** enables multimonitor adjustment synchronization.



SPECIAL CHARACTERISTICS

Carbon Footprint Meter, Carbon Savings Meter, ControlSync®, NaViSet® and NaViSet® Administrator compatible, sRGB Support, USB ver. 2.0 (4 down / 1 up), WindowsVistaCertifiedLogo



Energy Efficiency Ambient light sensor; Human sensor; Intelligent Power Management

Ecological Materials Downloadable manuals

| Technical Specification NEC MultiSync® EA224WMI | |
|---|--|
| DISPLAY | |
| Panel Technology | IPS TFT with W-LED backlight |
| Screen Size [inch/cm] | 21.5 / 54.61 |
| Screen Aspect Ratio | 16:9 |
| Pixel Pitch [mm] | 0.247 |
| Brightness (typ.) [cd/m ²] | 250 |
| Contrast Ratio (typ.) | 1000:1 (25000:1 (typ.) dynamic contrast ratio) |
| Viewing Angle [°] | 178 horizontal / 178 vertical (typ. at contrast ratio 10:1) |
| Response Time (typ.) [ms] | 14 |
| Colours [Mio.] | 16.7 |
| SYNCHRONISATION RATE | |
| Horizontal Frequency [kHz] | 31.5 - 83 |
| Vertical Frequency [Hz] | 56 - 75 |
| RESOLUTION | |
| Optimum Resolution | 1920 x 1080 at 60 Hz |
| Supported | 1920 x 1080; 1680 x 1050; 1600 x 1200; 1440 x 900; 1400 x 1050; 1366 x 768; 1360 x 768; 1280 x 1024; 1280 x 960; 1280 x 768; 1280 x 720; 1024 x 768; 800 x 600; 640 x 480 |
| CONNECTIVITY | |
| Digital | 1 x DVI-D (with HDCP); 1 x HDMI; USB ver. 2.0 (4 down / 1 up); 1 x DisplayPort |
| Analog | 1 x mini D-sub 15 pin |
| ELECTRICAL | |
| Power Consumption on Mode [W] | 15 (Eco Mode); 26 (max.) |
| Power Savings Mode [W] | < 0.43 |
| Power Supply | internal power supply |
| ENVIRONMENTAL CONDITIONS | |
| Operating Temperature [°C] | +5 to +35 |
| Operating Humidity [%] | 20 to 80 |
| ERGONOMICS | |
| Height adjustable Stand [mm] | 130 |
| Screen Tilt [°] | -5 to +30 |
| Screen Tilt / Swivel [°] | -170 to +170 |
| Screen Rotate [°] | 0 to 90 (landscape to portrait mode) |
| MECHANICAL | |
| Dimensions (W x H x D) [mm] | 507 x 370 x 218 |
| Weight [kg] | 5.6 |
| VESA Mounting [mm] | 100 x 100 |
| ADDITIONAL FEATURES | |
| Cable Management | yes |
| Kensington security slot | yes |
| Plug and Play | VESA DDCi; VESA DDC2B |
| Audio | Integrated Speakers (1 W + 1 W); Headphone Jack |
| Adjust Functions | Audio Volume / Lock-Out; Auto Adjust; Brightness; Colour Temperature Control; Contrast; Control Sync; DV Mode; EcoMode; Fine Adjust (analog); Human Sensing; Intelligent Power Management; Language Select; LED Brightness; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-Screen-Display (OSD) lock-out; One Touch Recovery; Power-Off Timer; sRGB |
| Shipping Content | Monitor; Power Cable; Control Sync Cable; USB Cable; Audio Cable; CD-ROM; Sales Office List; User Manual Signal Cable: VGA - VGA; DVI-D - DVI-D |
| Safety and Ergonomics | EPEAT™ Gold; CE; TCO 5.2; TÜV Ergonomics; TÜV GS; GEEA/ Energy Label; Energy Star 5.0; FCC Class B; PCT/Gost; UL/C-UL or CSA; ISO 9241-307 (pixel failure class I); MPR III; RoHS |
| Warranty | 3 years warranty incl. backlight |